



ELITE PLUS COLLECTION

60x120 CM

– VJWD - Oct. 2023







60X120 cm Vitrified Tiles

Johnson Vitrified Tiles Collection offers the most comprehensive range of quality tiles suitable for a wide range of interior styles and applications. Available in a size of 60 x 120 cm Johnson Vitrified Tile collection exhibits variety of colours, looks and finishes such as polished, matt, satin, wood and newly introduced glamour, exotic, radiant carwing and special carwing.

Ever evolving and ever inspiring, the collection will leave you spoilt for choice. Johnson Vitrified Tiles will lend unparalleled aesthetic appeal to your interior spaces.






60X120

EXOTIC	06
CARWING	12
POLISHED	14
MATT	26
TECHNICAL & PACKING DETAILS	32
BRANCH & EC DETAILS	33

BEIJING GREY





RANDOM PHASES


BEIRUT BROWN






RANDOM PHASES

BUDAPEST BLUE





RANDOM PHASES






<u>07</u> BEIJING GREY

EMPERADOR BRONZE



ENINBURGH BLUE -





RANDOM PHASES

FANTASY COFFEE






RANDOM PHASES



FLORIDA NERO





RANDOM PHASES

MAZONITE BLUE



MILAN GREY




THOM BLUE





RANDOM PHASES






11 THOM BLUE


ARIS STATUARIO





BERGO CREMA






RANDOM PHASES

SHIRE WHITE





RANDOM PHASES





ALEXNDRITE GREY



AMMOLITE ONYX





RANDOM PHASES

AMORITE GOLD





RANDOM PHASES





AMMOLITE ONYX

ANDOR ICE





RANDOM PHASES

BAIRSTOW CREMA





RANDOM PHASES

BOSSET PEARL





RANDOM PHASES



CARRARA SNOW





RANDOM PHASES

CHURCHIL CREMA





RANDOM PHASES

CUESTA CREMA





RANDOM PHASES

CUESTA GREY





RANDOM PHASES

CUESTA MOCHA





RANDOM PHASES

FEAZE BLUE






RANDOM PHASES



FLOURITE DOVE





RANDOM PHASES

FLOURITE UMBER





RANDOM PHASES

FORZENTA BEIGE





RANDOM PHASES

FORZENTA GREY






RANDOM PHASES

MILAN CELESTE





RANDOM PHASES

MIRINDA BUFF





RANDOM PHASES





21 FORZENTA GREY

MIRINDA STEEL





RANDOM PHASES

NATURA STATUARIO






RANDOM PHASES

PARSION CREMA





RANDOM PHASES



POMPEI BEIGE






RANDOM PHASES


PRINCE STATUARIO





RANDOM PHASES

ROSALIA BIANCO





RANDOM PHASES


SICILLIA BEIGE





RANDOM PHASES

THUNDER WHITE



VERNON PEARL





RANDOM PHASES





VERNON PEARL

DEODAR CEDAR





RANDOM PHASES

PINEWOOD CAMEL





RANDOM PHASES

RADCLIFF CHOCO





RANDOM PHASES






27 RADCLIFF CHOCO

A journey from tiles to lifestyles - measured in square feet

H&R Johnson (India) is a division of Prism Johnson Limited, one of India's foremost Integrated Building Materials conglomerates.

PRISM JOHNSON LIMITED



Established in 1958, Johnson is one of the oldest and trusted brands in the country. Built on the strong and unswerving foundations of quality and innovation, this trust has only grown in these decades gone by; and continues to grow. Starting with tiles, the brand soon diversified into offering lifestyle solutions in the realms of Engineered Marble & Quartz and Bath Solutions. There by becoming India's most Integrated Lifestyle Solutions brand. Every product that comes bearing the H&R Johnson insignia is a symbol of the same quality and innovation focused on adding value to the lives of our consumers.


Pioneering Innovations, A Way of Life

At H&R Johnson the term innovation is at the heart of everything we do. That's why it is backed by credible research. Every product attempts to fill in a void left by conventional offerings in the category, in an innovative manner. It's this value we place on cutting-edge innovation that makes us strive for more and eventually deliver more. A quality and a way of working that has redefine consumer lifestyles and expectations.

- Anti-skid & Water-repellent Tiles for Bathrooms
- · Rectified Wall Tiles
- · Johnson Marbonite Vitrified Wall and Floor Tiles
- Joint Free Tiles

- Large Format Slabs
- · Digitally Printed Wall & Floor Tiles
- · Germ Free Tiles & Sanitaryware
- Exterior & Industrial Flooring Solutions

India's Most Integrated Tile Manufacturing Company





Being India's most trusted tiling brand requires that trust to be maintained in every stage of developing each and every product that bears the name of the brand. That's why at H&R Johnson, our Felspar Mines are Self-owned, the soluble salts and inks are manufactured in-house, and even the dies and punches are made in-house. All, so that every step in the process comes with the same quality and assurance, that you expect from us.



Manufacturing Excellence

Johnson has the most modern manufacturing units across strategic locations in India. Our manufacturing facilities employ the best technology from world leaders in tile manufacturing equipment. All our plants are ISO compliant with both 9001 and 14001 certifications as well as OHSAS 18001 certification.



Certifications















Johnson is India's largest tile manufacturer. It's commitment to quality, service and innovation is backed by certification from the world's leading accreditation bodies.

ISO 9001: 2015

For implementing a Quality Management System for the Manufacture and Supply of Ceramic Tiles.

ISO 45001: 2018

For implementing an Occupational Health & Safely Management System for the Manufacturing of Ceramic Tiles.

ISO 14001: 2015

For implementing an Environmental Management system for the Manufacturing of Ceramic Tiles

Certificate of Merit for Energy Conservation, Bureau of Energy Efficiency, Ministry of Power A Recognition for the efficient use of energy and its conservation.

Plant has received Safety award by National Safety Council


GreenPro is a product certification given by the Confederation of Indian Industry (CII) which signifies environmentally conscious life cycle of the production; certification for eco-friendly products that helps customers make an informed choice towards sustainable products.

Grina

Griha council is a joint initiative of Ministry of New and Renewable Energy, GOI and The Energy and Resources Institute of implement Griha. India's national rating system for sustainable habitats

Johnson Tile Fixing Instructions

- 1. Plaster the surface of the floor where the tiles will be laid with smooth finish and complete the plastering and curing at least two weeks prior to laying.
- 2. Before fixing Porselano tiles lay them out in the desired pattern and make sure that they give an acceptable blend of shade, colour and design. Please note that certain amount of shade and size variation is inherent in the manufacture of vitrified ceramic tiles. Certain products will have I ntentional shade or colour variation to get the natural and elegant look, which is an integral element of the design resembling naturally created veins or shaded effect.
- 3. The company bears no responsibility towards the tiles exposed to any outside process like transfers, printing, firing etc.
- 4. For fixing Porselano, we recommend using an appropriate product from the range of tile fixing adhesives from the ARDEX ENDURA (INDIA) PVT. LTD. Please follow the adhesive manufacturer's recommendations and instructions for best results.
- 5. For fixing Porselano tiles on the floor, using sand and cement, follow the instructions given below:
 - a) Use cement and sand mortar in the ratio of 1:4. Add some water to create a consistent paste.
 - b) Once the mixing has been completed do not add any further water and use the same within one hour.
 - c) Apply a 20-30 mm layer of bedding material over an area of 1 square meter at a time on the surface of the area. Apply a fine slurry to the back of the tile to ensure proper and full bedding. Press gently for even adherence at the back of the tile. **DO NOTUSE AN IRON HAMMER OR SOME HEAVY MATERIAL TO PRESS THE TILE.**
- 6. For fixing Porselano tiles on Wall / Dado, we recommend using an appropriate product from the range of tile fixing adhesives from the ARDEX ENDURA (INDIA) PVT. LTD. with proper troweling method for 100 per cent coverage behind the tiles and for peerless bonding. Please follow the adhesive manufacturer's recommendations and instructions for best results. We do not recommend the use of sand and cement for fixing on Dado.
- 7. Mark and lay out the tiles from the center of the area to be laid so that cut tiles, if any, will be on the outer edges towards the walls.
- 8. The work size which we try to maintain for better technical performance is 60 cm x 60 cm on average. For large format tiles we do not recommend tiles to be laid without a gap. Plastic tile spacers can be used at each tile corner to maintain even grout lines between the tiles. It is advisable to maintain a gap of 2 mm to 6 mm between every tile to allow for possible expansion as per ISO tolerance norms.
- $9. \quad \text{Complete the laying process by pressing the cut Porselano tiles firmly into place along the walls/floors.}\\$
- 10. Allow 3-4 days for bed curing. After this period fill the joints with cementitious or epoxy grouts from ARDEX ENDURA (INDIA) PVT. LTD. Use of grout sealant is recommended for keeping the grout free of dust.
- 11. Fifteen minutes after finishing the grouting process, wipe off excess grout with a damp sponge and polish the tiles with a soft and dry cloth for a clean surface. The tiles can also be cleaned with a mild acid (However, Hydrofluoric acid and its derivatives should not be used). You can also use tile & stone cleaners from ARDEX ENDURA (INDIA) PVT. LTD.
- 12. Please note that the company does not accept any liability in case of problems arising out of non-adherence to these fixing instructions.
- 13. THE COMPANY WILL BEAR NO RESPONSIBILITY AFTER THE TILES ARE FIXED.
- 14. Kindly look for an arrow (→) on the back of the tile and follow the laying pattern as shown in Pic-1:-



NOTHING IN THESE INSTRUCTION IS A SUBSTITUTE FOR GOOD WORKMANSHIP AND SUPERVISION

ELITE PLUS

TECHNICAL SPECIFICATIONS __

S. No	Property	International Standard ISO 13006 / EN 14411 Group Bla Requirement	Indian Standard IS 15622:2017 Group Bla Requirement	Johnson Porselano Value (Matt)	Johnson Porselano Value (Polished)	Test Method
	Dimensions & Surface Quality	whichever is less applicable. Rectified edge	Rectified edge			
1	Deviation in Length & Width	± 0.3% or ±1.0mm	± 0.1 %	± 0.1%	± 0.1%	ISO 10545-2 / IS 13630-1
2	Deviation in Thickness	± 5% or ± 0.5mm	± 5 %	± 4%	± 4%	ISO 10545-2 / IS 13630-1
3	Straightness of Sides	± 0.3% or ±0.8mm	± 0.1 %	± 0.1%	± 0.1%	ISO 10545-2 / IS 13630-1
4	Rectangularity	± 0.3% or ± 1.5mm	± 0.1 %	± 0.1%	± 0.1%	ISO 10545-2 / IS 13630-1
5	Surface Flatness	± 0.4% or ±1.8mm	± 0. 5 %	± 0.2%	± 0.2%	ISO 10545-2 / IS 13630-1
6	Surface Quality	Min 95% free from visible defects	Min 95% free from visible defects	>95% free from visible defects	>95% free from visible defects	ISO 10545-2 / IS 13630-1
	Physical Property					
7	Water Absorption	≤ 0.5% individual Max 0.6%.	Average ≤0.08%, Individual 0.1%, Max	<u><</u> 0.05%	≤ 0.05%	ISO 10545-3/ IS 13630- 2
8	Modulus of Rupture	≥ 35 N/mm² Individual 32N/mm², Min	Average 35 N/mm² Individual 32N/mm², Min	≥ 38 N/mm²	≥ 38 N/mm²	ISO 10545-4/ IS 13630-6
9	Breaking Strength	700 N Min for thickness < 7.5 mm, 1300 Min for thickness ≥ 7.5 mm	700 N Min for thickness <7.5 mm, 1300 Min for thickness ≥7.5 mm	≥1500 N	≥ 1500 N	ISO 10545-4 / IS 13630-6
10	Moisture expansion	Report value	0.02 mm/m, Max	≤ 0.02 mm/m	≤ 0.02 mm/m	ISO 10545-10 / IS 13630-3
11	Scratch hardness of surface (Moh's scale)	Not Required	5, Min	≥ 6 (Matt surface)	≥ 5 (Polished surface)	IS 13630 -13
12	Resistance to Surface Abrasion of Glazed Tiles for Floor Application	report abrasion class & Cycle passed	Class II , Min	PEI III-V	PEI II- III	ISO 10545-7 /IS 13630 -11
13	Coefficient of Linear Thermal Expansion	Report value	Max, 6 x 10 ⁻⁶ K ⁻¹	≤6 x 10 ⁻⁶ K ⁻¹	≤ 6 x 10 ⁻⁶ K ⁻¹	ISO 10545-8/ IS 13630-4
14	Thermal Shock Resistance	Report result	10 cycles Min	No Damage	No damage	ISO 10545-9 / IS 13630 -5
15	Crazing Resistance of Glazed Tiles	Report result	4 cycles @7.5 bar Min	No Damage	No Damage	ISO 10545-11/ IS 13630-9
16	Impact Resistance	Report value	0.55, Min	≥ 0.55	≥ 0.55	ISO 10545-5 / IS 13630-14
17	Slip Resistance for Floor Application	Report value	Manufacturer to declare	≥ 0.45	≥ 0.4	ANSI B101.3
18	Frost Resistance	Report result	Required if requested by purchaser	No damage	No Damage	ISO 10545-12 / IS 13630-10
19	Bulk Density (g/cc)	Report value	2.2, Min	≥ 2.2	≥ 2.2	ASTM C373-16 / IS 13630-2
20	Color Resistance to UV light	Report result	-	No change in color	No change in color	DIN 51094
21	Chemical Property (cleansers except to cleansing agents containing Hydrofloric acids and its compounds)					
а	Resistance to Staining - Glazed Tiles	Min Class 3	Class I, Min	Class 3 (ISO) / Class 1(BIS)	Class 3 (ISO) / Class 1(BIS)	ISO 10545-14 / IS 13630-8
b	Resistance to Household Chemicals and Swimming Pool water cleansers - Glazed tiles	GB	AA Min	GA/AA	GA/AA	ISO 10545-13 / IS 13630-8
С	Resistance to acids and alkalis (glazed Tiles)	Report resistance class	Report resistance class	GA	GA	ISO 10545-13 /IS 13630 -8
22	Lead & Cadmium Release- for Glazed Tiles, where required	Report value	-	Nil	Nil	ISO 10545-15

^{*} ISO / IS technical specifications for Johnson tiles are applicable only for premium /Ist Quality tile Please inspect all tiles prior to installation, company will not entertain any complaints once tiles are laid / fixed

PACKAGING DETAILS ____

Product	Nominal	No of	Approx	Approx	Approx Cartons/	Approx Area per
	Size (cm)	Tiles/Box	Area/Box (sq m)	Weight/Box (kgs)	20' Container	Container (sq m)
Johnson 60x120 Wall Tiles	60x120	2	1.44	28	964	1388




YOU CAN ALSO REACH US AT _

Region	Branch	Tel.:
	Kolkata	033-46021880
	Bhubaneshwar	0674 6539836/37/2430240
East	Siliguri	9836065812
	Guwahati	8135846661/7575900492
	Ranchi	9576038118
	Mumbai	022-40647500
	Thane	022-25867600 / 666
	Pune	020-41301164 / 31
West	Aurangabad	8669600748
	Ahmedabad	079-48480010
	Raipur	0771-4919129
	Indore	0731-4007441
	Jalandhar	0182-4505038 / 39
North	Chandigarh	0172-4697100
	Delhi	011-49526600

Region	Branch	Tel.:	
	Jaipur	0141-2368329	
NI d	Lucknow	0522-2721699	
North	Varanasi	0542-2222620	
	Patna	9576038781	
	Bengalure	080-22234310/080-22234330	
	Hyderabad	040-29802270 / 71 / 72	
	Vijayawada	9666429666	
	Vishakhapatnam	0891-2796376	
	Tirupati	9121228960	
South	Kochi	0484-4871277	
South	Kozhikode	0422-4382698	
	Thiruvananthapuram	0471-2720141	
	Chennai	044-28544116 / 28541881	
	Coimbatore	0422-4382698	
	Madurai	0452-4355584 / 4355594	
	Trichy	9486718544	

EXPERIENCE CENTERS

Location	Address	Tel.:
Kolkatta	HOUSE OF JOHNSON - 83 JBS Haldane Avenue, TOPSIA Trinity towers Kolkata - 700046	033-46021880
Guwahati	HOUSE OF JOHNSON - 1st Floor, Above Royal Riders Honda, Near Rahul Kata, Pub Bragaon, Garchuk, Guwahati - 781035	7575900492
Bhubaneshwar	HOUSE OF JOHNSON - Ray Tower, 1st Floor, N4/237, Indradhanu market, IRC Village, Nayapalli, Bhubaneshwar, Orissa - 751015	0674 6539836/37/2430240
Patna	HOUSE OF JOHNSON – SK Builders and colonizer Pvt.Ltd.,1st Floor, SK Palace, Saguna more, Bihar – 801503.	9702651243
Chandigarh	HOUSE OF JOHNSON - SCO 214, sector14, Panchkula, Haryana - 134109	0172-4637724
Delhi	HOUSE OF JOHNSON - First & Mezzanine Floor, B-1/G-3, Mohan Industrial Estate, Mathura Road, New Delhi - 110094.	11-49526600
Lucknow	HOUSE OF JOHNSON - 1st Floor, Prithvi Ratan Height, Plot No CP-4, Vijayant khand - 3, Gomtinagar Yojna, Lucknow - 226028	0522-2721699
Varanasi	HOUSE OF JOHNSON - Ashakunj, 1st floor, D59/103 D4, Opp Siddharth Complex, Sigra Mehmoorganj Road, Varanasi - 221010	0542-2222620
Aurangabad	House Of Johnson Aurangabad - Gut No 16/44, NH-211, Near Balapur Phata, Near Ramkisan Lawns, Beed Bypass Road Aurangabad 431005	8669600748
Pune	HOUSE OF JOHNSON - Sable House, Poona Snuff Factory, Sr. No 11A, Plot 408/4/5, Satara Road, Gultekadi, Pune - 411037	7350009364
Thane	HOUSE OF JOHNSON - Shop No.5, Gr.Floor, Cosmos Jewels, Near Dmart, Anand Nagar, Ghodbunder Road, Thane West - 400615	8424003247
Mumbai - Andheri	HOUSE OF JOHNSON - 1st flr, Bonanza, Sahar Plaza, Nr Hotel Kohinoor continental, J B Nagar, Andheri Kurla Road, Andheri East, Mumbai - 400059	8108030975
Ahmedabad	HOUSE OF JOHNSON - F 106-107, Shivalik Plaza, IIM Road, Panjrapole Cross Road, Ahmedabad, Gujarat - 380015	079-48480010
Indore	HOUSE OF JOHNSON - Shop No 5, 6, 7 and 8, Upper Ground Floor, Exotica, Shalimar Township, Village Niranjanpur, A. B. Road, Indore, Madhya Pradesh - 452001	0731-4007441
Raipur	HOUSE OF JOHNSON - 2nd Floor, MM Silver Plaza, Opp Udyog Bhawan, Ring Road - 1, Raipur, Chattisgarh - 492001	771-4919129
Coimbatore	HOUSE OF JOHNSON - Elysium Towers, Park Gate Rd, No. 21, ATT Colony, Gopalapuram, Coimbatore - 641018	0422-4382698
Chennai	HOUSE OF JOHNSON - 82, 84 & 86 Bascon Maeru, 1st floor, Kodambakkam High Road, Nungambakkam, Chennai - 600034	044-48611632
Kochi	HOUSE OF JOHNSON - Door no. 11/300 f, Next to VTJ Hyundai, NH 47 Kundanoor, Maradu, Kochi, Ernakulam - 682304	0484-4871277
Kozhikode	HOUSE OF JOHNSON - Tilal Tower, Near Nexa Showroom, Kudilthod, Malaparamba bypass, Kozikode, Kerala - 673017	0495-2357505
Thiruvananthapuram	HOUSE OF JOHNSON -1st Floor, Sreedhanya Apex, TC 22/3720 (4) Vellayambalam, Sasthamangalam PO, Thiruvananthapuram, Kerala - 695010	0471-2720141
Bengalure	HOUSE OF JOHNSON - No.39, Rajaram Mohan Roy Road , Opp. Kanteerava indoor Stadium, Bengalure - 560027	080-22234310/080-22234330
Bengalure	HOUSE OF JOHNSON - Dodda Banaswadi, Opp. New Baldwin Residential School, Bengalure-560043	080-41692976 / 41692060
Hyderabad	HOUSE OF JOHNSON - SP Jubilee Crown (3rd Floor) Plot - 1270, Road No.36, Jubilee Hills, Hyderabad – 500033	8897525143





NOTES	



Toll Free No.: 1800-210-7484 WhatsApp No.: +91 84510 57484 **Email:** tiles.customercare@prismjohnson.in

For Export Enquires, Email:

exports.customercare@prismjohnson.in

PRISM JOHNSON LIMITED

H&R JOHNSON (INDIA) DIVISION Corporate Office:

7th Floor, Windsor, C. S. T. Road, Kalina, Santacruz (East), Mumbai - 400 098, India.

Tel: +91-22-40647300

Website: www.hrjohnsonindia.com

Registered Office: 305, Laxmi Niwas Apartments, Ameerpet

Hyderabad - 500016, Telangana, India.

Download App





Download E-Catalogue







@hrjohnsonofficial
W Hrjohnsonindia
O hrjohnson_india









